

# **ORDER ACKNOWLEDGEMENT**

#### CONFIGURATION

Chassis	Free Issue DAF 4x2	
Body	Mini Olympus OL8	
Bin Lift	Integral Bar Lift	772

# FREE ISSUE CHASSIS SPECIFICATION

Vehicle Overview	
Chassis Model	DAF LF 230 4x2
Cab Type	Day cab
GVW(kg)	12,000
Wheelbase(mm)	3550mm
Engine	Euro 6 PX-7 (172kW/234BHP) 6-Cylinder 6.7L
Gearbox	Allison 3000 Series 5-speed Automatic
Fuel Tank	110 litres LHS
PTO	Dennis Eagle/Terberg to supply the PTO to fit onto the Allison transmission
Exhaust	Vertical
	2,1m Wing Mirrors 03605 Mirror brackets, body 2.10-2.29 m Application for refuse 09240 Application connector for refuse collector
Additional Requirements	Body attachments 07487 Body attachment BAM 1
	Body Builder Module Full 09952 Body Builder Module (BBM) full
	CAN J1939 Functions ****** J1939 Application connector (Chassis: A105: Cab A106)
	Relocate Allison ECU for PTO fitment. No air tanks in AE. No oil cooler in AE.

# **TYRES & SUSPENSION**

Axle	Design Weight (kg)	Suspension	Tyres
Axle 1	4,500	Parabolic Spring	245/70R22.5
Axle 2	8,500	Full Air	245/70R22.5
	Tyre Manufacturer	Goodyear	

#### STANDARD EQUIPMENT - BODY

	Mini	Olympus OL8	
Body Volume (m³)	8.0	Hopper Volume (m³) 1.0	
- CE approved - EN1501	-1:2011 & EN1501-5:2011	- Side mounted hopper lift rams	
- Smooth sided one pied	e construction	- Integral hopper safety prop	
- Low centre of gravity		- Integrated diagnostics display	
- Fully integrated CANbu	us logic system	- Body cycle & run hour display in monitor	
- In-cab control panel &	CCTV colour monitor	- Full height hopper seals	
- Quiet & efficient hydra	ulic system	- Front of body drain hose	
- In-cab & dual controls		- High tensile steel ejection plate	
- Short rear overhang		Heavy duty packer plate	
- Waterproof front mounted electrical junction box		15 second cycle time (nominal)	
- 'Sealed for life' bearings		Hydraulic tank c/w remote pressure fill	
- Rear view camera		10 micron return line filter	
- Water dam at front of body		5mm tailgate floor	
- Number & colour coded wiring		LED side marker lights	
- IP67 wiring & IP69 switches		LED high & low level rear lights	
- Interlocks prevent operation unless tailgate down		1 x hopper load lamp	
- Inverted sweep rams & external pack rams		2 x front-facing grill-mounted amber directional beacon	



# FITTED EQUIPMENT - BODY

Option No.	Option Name
5108001	Lateral Protection Device (Fixed)
2052020	Pack On The Move (Single Cycle)
2054040	Hopper Drain Valve
5064002	Discharge Chute (Rear of Body)
2101010	External Discharge Controls
2071020	Side Access Door
2000000	Hand Wash Unit (fitted Offside of the vehicle)
2000000	Reverse Alarm (Loudmouth)
	ISS FORS DVS Package
2000000	ISS-I-DCS-ISS Dual Camera System
	ISS-I-CYCDT-Cyclear Intelligent Detection System

# FITTED EQUIPMENT - LIGHTING (BEACONS)

Option No.	Option Name
2000010	LED Rear of Body Beacons (2 Side + 2 Rear)
2127081	Front of Body Beacon
2000010	LED Work Station Light

## **INTEGRAL BAR LIFT**

Option No.	Option Name
5010001	Integral Bar Lift designed especially for the Olympus Mini and welded to tailgate. Standard equipment includes:  - Electro hydraulic lifter control by means of buttons  - Equipped with mechanical combs and cover catchers  - Suitable for EN840-1 containers, EN840-2 containers, EN840-3 containers (front loading by comb  - Autogather  - Lifting capacity 500kg

## WARRANTY

Option No.	Option Name
5000000	Body & Integrated Bar Lift Warranty (3 Year Full)

## **TRAINING**

Option No.	Option Name
5000000	Body & Integrated Bar Lift Training (Operator Instruction)

## **PAINT DETAILS**

aint Specification	[1] [1] [2] [2] [2] [2] [2] [2] [2] [2] [2] [2
Cab	As per chassis manufacturer - Brilliant White H3279WHTE
Chassis	As per chassis manufacturer – Stone Grey
Hopper	Brilliant White H3279/1
Integral Bar Lift	Brilliant White H3279/1
Conspicuity Tape	White
DE / Terberg Logo	Yes

<sup>&</sup>quot;All self-coloured plastic items will remain unpainted".